Safety data sheet

(According to Regulation (EC) 1907/2006)



Recron® Polyester High Tenacity Yarn

Polyester Sector

1. **IDENTIFICATION OF SUBSTANCE/ PREPARATION AND COMPANY/ UNDERTAKING**

1.1 Identification of the product:

Recron® Polyester High Tenacity Yarn Product name:

Production of Technical textile products. Mechanical rubber goods. Sewing 1.2 Use of the product:

threads, ropes & Cordage and other related products.

1.3 Company/ Undertaking identification

1.3.1 Manufacturer: Reliance Industries Ltd.

(Polvester Sector)

Reliance Corporate Park, Building No. 8, 'B' Wing, First Floor, Opposite Ghansoli Railway Station, Thane Belapur Road, Navi Mumbai - 400 701, INDIA

Tel: +91-22-44770000 Fax: +91-22-44779107

E-mail address of person responsible for the Safety Data Sheet:

girish.c.desai@ril.com

+91-261-2835050 OR +91-261-2835056 1.3.2 Emergency telephone:

(24 x 7) Site Shift Manager, Hazira Division

1.4 **REACH Only** Attn: Mr James Searles

Representative Steptoe & Johnson LLP

240 Avenue Louise, 1050 Brussels, Belgium Tel: +3226260500, Fax: +3226260510

Email: jsearles@steptoe.com

2. **HAZARDS IDENTIFICATION**

Hazard Codes: Not applicable Risk phrases: Not applicable Safety phrases: Not applicable

This product is not considered hazardous or toxic. The hazards if any are associated with its processing. Polymer dust and spinfinish fumes may represent a fire hazard at sufficient concentrations in presence of ignition sources.

3. **COMPOSITION/ INFORMATION ON INGREDIENTS**

3.1 Composition:

| Chemical identity | CAS No | EINECS/ ELINCS No | Concentration |
|--------------------------------------|------------|-------------------|---------------|
| Polymer (Polyethylene terephthalate) | 25038-59-9 | Not listed | > 98.5% |
| Spin finish | - | - | < 1.5% |
| Hazardous ingredient | | | None |

3.2 Classification according to 1999/45/EC:

Not applicable (not a dangerous preparation)

3.3 Remarks on special components:

The products and their constituents are not dangerous. The products do contain oil that serves as a processing aid and may generally be removed in an aqueous medium, if so required.

Version: 1.3 Page 1 of 6 Issue Date: 11 May 2017

Safety data sheet

(According to Regulation (EC) 1907/2006)



Recron® Polyester High Tenacity Yarn

Polyester Sector

FIRST AID MEASURES

4.1 Inhalation: Inhalation of snow dust and finish decomposition products should be

avoided by hood suction and fresh air ventilation. In case of coughing or other symptoms the person should seek fresh air and if necessary, see

a physician.

4.2 Skin contact: Wash with soap and water. If irritation develops, consult a physician.

4.3 Eye contact: The eyes should be washed immediately with plenty of water. If irritation

continues, consult a physician.

4.4 Ingestion: Do not induce vomiting. Call in a physician and show him this data

sheet.

5. **FIRE-FIGHTING MEASURES**

5.1 **Burning behaviour:**

> Flammable class: Not determined

Flash point: Not applicable. Product burns in fire.

Self-ignition temperature: 515 °C DIN 51794

> 300 °C Decomposition temperature:

5.2 Suitable extinguishing media: Dry Chemical Powder, CO₂ or Water Spray (see 5.3 below)

5.3 Extinguishing media which

must not be used for safety reasons:

Special exposure hazards in a

fire:

5.4

Low fire hazard. Polymer dust & fumes may represent a fire hazard at sufficient concentrations. On complete combustion, the major products

Do not use water, if fire is caused by an electrical short circuit.

formed are carbon dioxide & water. Remove ignition sources. Beware of

electrostatic charges.

5.5 Special protective equipment

for fire-fighters:

Wear self-contained breathing apparatus, protective clothing and

headgear to prevent contact with skin & eyes.

6. **ACCIDENTAL RELEASE MEASURES**

Personal precautions: Use normal personal protection.

Environmental precautions: In case of accidental spills, do not allow entering drains and waterways.

When picked up, treat material as prescribed under section 13 (Disposal

considerations).

Clean up by vacuuming, physical picking or mechanical means. Methods for cleaning up:

> If cleaning up involves the use of water, the wastewater should be given the appropriate treatment in an effluent treatment plant, in line with local

regulations.

Safety data sheet

(According to Regulation (EC) 1907/2006)



Recron® Polyester High Tenacity Yarn

Polyester Sector

7. **HANDLING AND STORAGE**

7.1 Handling: Normal handling and processing does not require special technical protective

measures. Avoid formation of dust.

Accumulation of polymer dust may represent at sufficient concentrations a fire and explosion hazard. Remove ignition sources. Beware of electrostatic

If subsequent processing involves the use of water, the wastewater should be

given the appropriate treatment in an effluent treatment plant, in line with

local regulations.

7.2 Store at ambient temperatures. Storage:

Bobbins/ beams/ cartons must be stored in line with existing provisions.

Existing fire protection measures have to be followed.

Do not store near flame, ignition sources, direct sunlight or incompatible materials. Maintain good housekeeping to control dust accumulations.

EXPOSURE CONTROLS / PERSONAL PROTECTION 8.

8.1 **Exposure limit values:** Comply with national occupational threshold values for dust. According to

TRGS 900 (Germany) there are two values:

a) 3 mg/m³ - for fine dust

b) 10 mg/m³ - for coarse dust

8.2 Avoid accumulation of and contact with dust and finish decomposition **Exposure controls:**

products by hood suction, sufficient fresh air supply and proper house

keeping.

8.2.1 Occupational exposure controls:

No special measures required, except for fire or insufficient hood suction / a) Respiratory protection: fresh air supply (see 4 and 5).

b) Hand protection:



Protective gloves are required while cutting carton straps or filament waste.

c) Eye protection:



Wear safety glasses (e.g. especially while cutting carton straps).

d) Skin protection:

No special measures required. Yarns that are processed at high speeds may cause abrasions or cuts. Appropriate protective measures are recommended.

8.2.2 Environmental exposure

controls:

Exhausted dust and finish decomposition products shall be kept back efficiently by adequate filter systems.

Version: 1.3 Supersedes: V1.2 dated 10 December 2013

Safety data sheet

(According to Regulation (EC) 1907/2006)



Recron® Polyester High Tenacity Yarn

Polyester Sector

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 General information

Appearance Solid (form: Bobbin, Beam)
Colour Raw-white, white or dyed

Odour Odourless

9.2 Important health, safety and environmental information

pH Not applicable

Melting point/range 240 - 260 °C

Flash point Data not available

Flammability Data not available

Explosive properties Data not available

Oxidising properties None

Vapour pressure Not applicable Relative density $1.3 - 1.4 \text{ g/cm}^3$

Solubility Insoluble in common solvents.

Water solubility Insoluble
Partition coefficient: Not applicable
Viscosity Not applicable
Vapour density Not applicable
Evaporation rate Not applicable

10. STABILITY AND REACTIVITY

10.1 Conditions to avoid: Material is stable under normal conditions.

Temperatures above 300 °C lead to thermal decomposition (see also 5.6)

10.2 Materials to avoid: Strong oxidation agents as well as strong acids and caustic will decompose

polyester.

Acetic anhydride, acetone, aniline, benzene, chloroform, chromic acid, cyclohexanone, dimethylformamide, dioxane, ethyl acetate, methyl ethyl ketone, methylene chloride, phenol, tetrahydrofuran, trichloroethylene,

triethanolamine, caustic soda.

10.3 Hazardous decomposition

products:

Above the decomposition temperature, the major volatiles will be terephthalic acid, oligomers of PET, carbon dioxide, carbon monoxide, acetaldehyde, and

low molecular weight alcohols/ aldehydes.

If heated to 150-250 °C during processing, the filament lubricants can degrade and generate off gases, which may contains small amounts of chemicals such as aldehydes, alcohols, acetic acid, acetone, etc.

We are not aware of chemicals such as these reaching concentrations that present a serious health hazards. However, information on toxic effects and recommended exposure limits of these and other chemicals can be found in the most recent edition of the ACGIH documentation of threshold limit values.

When Polyester Filament Yarn is burned, no unusual combustion gases have been observed, and its combustion products are similar to those of other organic materials composed of the same elements.

Issue Date: 11 May 2017

Safety data sheet

(According to Regulation (EC) 1907/2006)



Recron® Polyester High Tenacity Yarn

Polyester Sector

11. TOXICOLOGICAL INFORMATION

11.1 Acute toxicity Low oral toxicity

11.2 Inhalation Low acute toxicity. Dusts and vapours or fumes evolved during thermal

processing may cause irritation to the respiratory system.

11.3 Ingestion Data not available

11.4 Skin irritation No evidence of irritant effect from normal handling and use.

11.5 Eye irritation Dust and fumes generated during processing may have irritant effect on

eyes. Permanent damage is unlikely.

Recron® Polyester High Tenacity Yarn is a non-toxic man-made fibre. Proper use has not been associated with any special hazard or any detrimental effects on health.

12. ECOLOGICAL INFORMATION

12.1 Eco-toxicity: Low toxic to aquatic organisms. The filament yarn product can be separated

out mechanically. Some finish components may vaporize or decompose at

temperatures above 130 °C.

If subsequent processing involves the use of water, the wastewater should be given the appropriate treatment in a purifying plant, in line with local

regulations.

12.2 Mobility: The product is insoluble in water. Due to their negligible solubility in water

and high molecular weight, they are expected to have a low BOD and will

not cause oxygen depletion in aquatic systems.

12.3 Persistence and

degradability:

The product is non-biodegradable in soil.

12.4 Bio accumulative potential: They are expected to be non-biodegradable and unlikely to bio-concentrate.

12.5 Other adverse effects: Unlikely to affect biological treatment processes.

13. DISPOSAL CONSIDERATIONS

Disposal of Polyester product does not pose any specific danger.

It is recommended that Polyester Filament yarns & waste be recycled.

If recycling is not possible, Polyester waste yarns & waste can be disposed of in a suitable refuse installation or incinerated subject to local regulations.

14. TRANSPORT INFORMATION

14.1 UN number: Not applicable14.2 Class/ Packing group: Not restricted

14.3 Marine pollutant: None

14.4 International Transport

Regulations:

Not classified as dangerous for transport

14.5 Road / Rail (ADR / RID): Not restricted
14.6 Sea (IMDG): Not restricted
14.7 Air (ICAO / IATA): Not restricted

Version: 1.3
Supersedes: V1.2 dated 10 December 2013

Safety data sheet

(According to Regulation (EC) 1907/2006)



Recron® Polyester High Tenacity Yarn

Polyester Sector

15. REGULATORY INFORMATION

Recron® Polyester products do not require hazard warning labels in accordance with EC directives.

Risk phrase(s): Not applicable Safety phrase(s): Not applicable

16. OTHER INFORMATION

16.1 Recommended restrictions on use:

This safety data sheet is provided for the products and their applications as specified in Section 1. The safety data sheet is not written with the individual end-user in mind.

It is recommended that supplementary information be requested if an unusual application of these products is intended.

Consult the manufacturer if the product(s) is to be used for special applications (such as, but not limited to, the food, hygienic, medical or surgical sectors) or for new end-uses.

16.2 Further information:

Recron® Polyester High Tenacity Yarn is an article made of man made fibres and is not subject to European Regulation (EC) 1907/2006 on registration, evaluation and authorization of chemical substances (REACH). Safety Data Sheets or Chemical Safety Reports according to Art. 31 of this regulation are therefore not required.

This data sheet was established following Annex-II of this regulation. The raw materials and auxiliaries used for the manufacturing of Recron® Polyester High Tenacity Yarn are predominantly concerned by this regulation. Reliance will track the status of the registration and evaluation of these materials.

16.3 Disclaimer:

This Safety Data Sheet and the health, safety and environmental information it contains are intended to provide a summary of our knowledge and guidance regarding use of the designated Product. Its contents are offered in good faith as accurate and complete as of the date specified below, but without guarantee. The data herein applies only to the Product sold by entities of the Reliance group and not to products sold by others. It relates only to the Product and does not relate to its use in combination with any other product or material or in any process.

Local laws and regulations and conditions of use and suitability of the product for particular uses are beyond the control of Reliance; all risks of use, storage, handling, transportation and disposal of the Product are therefore assumed by the user and Reliance expressly disclaims all warranties of every kind and nature, including warranties of merchantability and fitness for a particular purpose in respect to the use or suitability of the Product. Reliance shall not be responsible for any damage or injury resulting from abnormal use of the Product, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the Product.

Appropriate warnings and safe handling procedures should be provided to all handlers and users. In the case of a user in the European Union, as per Article 34 of REACH Regulation (EC) No. 1907/2006, user shall communicate to Reliance any new information on hazardous properties of the Product and/or new information relevant to risk management measures for the identified uses.

Alteration or re-publication of this document in whole or part is strictly prohibited.

Revisions: 16.4

Version: 1.1 - Contact details of "REACH" Only Representative included as section1.4. Manufacturer office address

changed.

Version: 1.2 - Reaffirmed Version: 1.3 - Reaffirmed

Version: 1.3 Page 6 of 6 Issue Date: 11 May 2017